


# BUCKINGHAM MFG.

## BIG BUCK WRAP PAD

MODEL NO. 3202C & 32021C series - Angled Style Wrap Pad  
3204C & 32041C series - Straight Style Wrap Pad.


(Angled Style Wrap Pad shown throughout these instructions)



(Right Side shown)

### Assembling Pad to Climber

1. Squeeze the pad so the tunnel protrudes outward, away from the pad.
2. Properly orientate climber and push the sleeve (attached to climber) from the bottom upward until the sleeve loop is exposed in the tunnel slot.
3. Adjust the length of the climber using the adjustable climber sleeve so that the top of pad is 1/2" below the projecting knee bone. (Fig. 'A')
4. Slide the sleeve retaining strap under the climber sleeve loop and metal insert loop and pull sleeve retaining strap through both loops.
5. Adhere the sleeve retaining strap to the loop fastener on the pad.



### Attaching Pad to Leg

1. Place your foot on the stirrup of the climber with padded fabric portion facing toward the inside of your leg.
2. To secure the pad to your leg, begin by threading the hook and loop strap through the steel loop. (Fig. 'B' and Fig. 'C')
3. Continue to pull the hook and loop strap through the steel loop until the pad is snug on the leg. *Always* ensure that the MINIMUM WRAP LABEL has been pulled through the steel loop. This ensures a proper wrap. Failure to do so may cause release, resulting in serious injury or death. (Fig. 'C' and Fig. 'D')



Fig. 'A'



Fig. 'B'



Fig. 'C'

4. Wrap the free end around the pad, adhering the hook fastener to the loop fastener on the body of the pad. (Fig. 'D')

\*Note: Attach and fasten foot strap for climber after attaching pad to leg. (Fig 'A' and 'E')



Fig. 'D'

## Cleaning

Proper maintenance and storage of your equipment will prolong its useful life and contribute toward its performance.

Nylon should be cleaned with mild soap and water and be allowed to air dry thoroughly without using excessive heat. Do not use any type of corrosive substance or acid, which will gradually eat away the fabric.

Clean hook & loop fasteners with a soft bristle brush.

Clean leather by removing surface dirt with a clean cloth dampened (not wet) with water and allow to air dry.



Fig. 'E'

**BUCKINGHAM MFG. CO., INC.**  
 BINGHAMTON, NY  
 1-800-937-2825  
 Fax 607-773-2425  
 e-mail - sales@buckinghammfg.com

Information contained in these written instructions supersedes all other information (written, audio, video etc. produced by Buckingham Mfg. prior to the revision date of this document.