

# BUCK $\Omega$ HM™

## DIELECTRIC HARNESSSES

Buckingham's new Dielectric Harness were designed for working conditions with electrical hazards making this a great option for substation, distribution, and other utility work. Dielectric hardware eliminates the potential of electricity being transferred through steel hardware if working around an energized conductor in wet or damp conditions. Dielectric hardware also provides a better resistance to corrosion in extreme conditions (hot/humid or salty air environments).



### BuckOhm™ H-Style Harness 68L9EQ12

Features include:

- 9KV rated Dielectric hardware.
- Lightweight
- Dielectric quick connect chest buckle.
- Dielectric dorsal D-Ring.
- Dual trauma straps.
- Arc rated shoulder pads.
- Dielectric quick connect leg strap buckles for easy donning.
- Dielectric friction buckles on vertical shoulder straps for height adjustments.
- Available in S, M, L and XL sizes.

*Meets or exceeds ASTM F887 Electric Arc Performance Requirements & ANSI Z359.*

### BuckOhm™ H-Style Harness w/Pigtail 68L9EQ17

Features include:

- 9KV rated Dielectric hardware
- Lightweight
- Dielectric quick connect chest buckle
- 18" Dorsal Pigtail w/3KV Dielectric D-Ring
- Dual trauma straps
- Arc rated shoulder pads
- Dielectric quick connect leg strap buckles for easy donning
- Dielectric friction buckles on vertical shoulder straps for height adjustments
- Available in S, M, L and XL sizes.

*Meets or exceeds ASTM F887 Electric Arc Performance Requirements & ANSI Z359.*



### BuckOhm™ X-Style Harness 603A8Q1

Features include:

- 9KV rated Dielectric hardware
- Featured in the popular BuckViz Safety Green™ nylon webbing
- Lightweight
- Dielectric quick connect buckles on leg straps and torso for easy donning
- Web loop dorsal attachment
- Web loop sternal attachment
- Dual trauma straps
- Dual parking attachments
- Arc rated shoulder pads
- Available in S, M, L and XL sizes.

*Meets or exceeds ASTM F887 Electric Arc Performance Requirements & ANSI Z359.*

# BUCK ΩHM™

## BLACK DIELECTRIC HARNESSSES



**BuckOhm™ Black  
H-Style Harness  
68L9EQ21**

Features include:

- 9KV rated Dielectric hardware.
- Lightweight
- Dielectric quick connect chest buckle.
- Dielectric dorsal D-Ring.
- Dual trauma straps.
- Arc rated shoulder pads.
- Dielectric quick connect leg strap buckles for easy donning.
- Dielectric friction buckles on vertical shoulder straps for height adjustments.
- Available in S, M, L and XL sizes.

*Meets or exceeds ASTM F887 Electric Arc Performance Requirements & ANSI Z359.*

**BuckOhm™ Black  
H-Style Harness w/Pigtail  
68L9EQ22**

Features include:

- 9KV rated Dielectric hardware
- Lightweight
- Dielectric quick connect chest buckle
- 18" Dorsal Pigtail w/3KV Dielectric D-Ring
- Dual trauma straps
- Arc rated shoulder pads
- Dielectric quick connect leg strap buckles for easy donning
- Dielectric friction buckles on vertical shoulder straps for height adjustments
- Available in S, M, L and XL sizes.

*Meets or exceeds ASTM F887 Electric Arc Performance Requirements & ANSI Z359.*



**BuckOhm™ Black  
X-Style Harness  
603A8Q4**

Features include:

- 9KV rated Dielectric hardware
- Lightweight
- Dielectric quick connect buckles on leg straps and torso for easy donning
- Web loop dorsal attachment
- Web loop sternal attachment
- Dual trauma straps
- Dual parking attachments
- Arc rated shoulder pads
- Available in S, M, L and XL sizes.

*Meets or exceeds ASTM F887 Electric Arc Performance Requirements & ANSI Z359.*