

BUCK Ω HM™

DIELECTRIC BUCKYARD

Introducing the new BuckOhm™ BuckYard, a energy absorbing lanyard with dielectric hardware! This new lanyard is available in two color options; BuckViz Safety Green™ or Black. The new BuckOhm™ line of energy absorbing lanyards are designed for working conditions with electrical hazards, making this a great option for substation, distribution and other utility work.

BUCKOHM™ BUCKYARD



**BuckOhm™
BuckYard**
84+G1D16S1

Features Include:

- Dielectric locking snap hook on one end and web loop on the other end.
- Web loop can be hitched to a dielectric or steel D-ring.
- Dielectric snaps can be attached to a web loop (with wear guard), dielectric or steel D-ring.
- Interior materials stretch to reduce the arresting force to less than 900 lbs.



**BuckOhm™
BuckYard**
8+G+G1D16S1

Features Include:

- Dielectric locking snap hook on both ends.
- Web loop can be hitched to a dielectric or steel D-ring. Dielectric snaps can be attached to a web loop (with wear guard), dielectric or steel D-ring.
- Interior materials stretch to reduce the arresting force to less than 900 lbs.

Meets or exceeds ASTM F887 Electric Arc Performance Requirements & ANSI Z359

BUCKOHM™ BUCKYARD STRETCH

The BuckYard Stretch™ expands/stretches when working. A 6' lanyard will expand/stretch to 6' when working and will retract to 44", minimizing the length of webbing the end user has while working.



**BuckOhm™
BuckYard Stretch**
84+G7D16S1

Features Include:

- Dielectric Snap Hook on one end & web loop on other end.
- Web loop can be hitched to a dielectric or steel D-ring. Dielectric snaps can be attached to a web loop (with wear guard), dielectric or steel D-ring.
- Interior materials stretch to reduce the arresting force to less than 900 lbs.



**BuckOhm™
BuckYard Stretch**
8+G+G7D16S1

Features Include:

- Dielectric locking snap hooks on both ends.
- Web loop can be hitched to a dielectric or steel D-ring. Dielectric snaps can be attached to a web loop (with wear guard), dielectric or steel D-ring.
- Interior materials stretch to reduce the arresting force to less than 900 lbs.

Meets or exceeds ASTM F887 Electric Arc Performance Requirements & ANSI Z359

BUCK ΩHM™

BLACK BUCKYARD

BUCKOHM™ BLACK BUCKYARD



BuckOhm™
Black BuckYard
84+G1E16S1

Features Include:

- Dielectric locking snap hook on one end and web loop on the other end.
- Web loop can be hitched to a dielectric or steel D-ring. Dielectric snaps can be attached to a web loop (with wear guard), dielectric or steel D-ring.
- Interior materials stretch to reduce the arresting force to less than 900 lbs.



BuckOhm™
Black BuckYard
8+G+G1E16S1

Features Include:

- Dielectric locking snap hook on both ends.
- Web loop can be hitched to a dielectric or steel D-ring. Dielectric snaps can be attached to a web loop (with wear guard), dielectric or steel D-ring.
- Interior materials stretch to reduce the arresting force to less than 900 lbs.

Meets or exceeds ASTM F887 Electric Arc Performance Requirements & ANSI Z359

BUCKOHM™ BLACK BUCKYARD STRETCH

The BuckYard Stretch™ expands/stretching when working. A 6' lanyard will expand/stretch to 6' when working and will retract to 44", minimizing the length of webbing the end user has while working.



BuckOhm™ Black
BuckYard Stretch
84+G7E16S1

Features Include:

- Dielectric Snap Hook on one end & web loop on other end.
- Web loop can be hitched to a dielectric or steel D-ring. Dielectric snaps can be attached to a web loop (with wear guard), dielectric or steel D-ring.
- Interior materials stretch to reduce the arresting force to less than 900 lbs.



BuckOhm™ Black
BuckYard Stretch
8+G+G7E16S1

Features Include:

- Dielectric locking snap hooks on both ends.
- Web loop can be hitched to a dielectric or steel D-ring. Dielectric snaps can be attached to a web loop (with wear guard), dielectric or steel D-ring.
- Interior materials stretch to reduce the arresting force to less than 900 lbs.

Meets or exceeds ASTM F887 Electric Arc Performance Requirements & ANSI Z359