

Universe	Professional
Type	Verticality
Category	Connectors
Subcategory	Ultra-light carabiners



Sm'D

The compact Sm'D asymmetrical aluminum carabiner is recommended for workers at height looking to reduce weight to a minimum. Its D shape makes it especially suitable for attaching devices. Available with or without two locking systems: automatic TRIACT-LOCK system or manual SCREW-LOCK system.

Short Description Ultra-light asymmetrical carabiner





Selling Points



- Compact aluminum carabiner, for workers at height looking to reduce weight to a minimum
- D shape is especially suitable for attaching devices
- Facilitates manipulations:
 - fluid interior design limits the risk of having a catch point and facilitates rotation of the carabiner
 - Keylock system to avoid any involuntary snagging of the carabiner
- H profile:
 - ensures an optimal strength/weight ratio
 - protects markings from abrasion
- Hole for connecting TIBLOC or MICRO TRAXION type devices, limiting the risk of losing them
- Available without locking system, for easy clipping during progression using climbing techniques
- Two locking systems available:
 - TRIACT-LOCK: automatic locking with triple-action gate opening
 - SCREW-LOCK: the manual screw-lock with red band provides a visual warning when the carabiner is unlocked
- Also available in black

Specification

- Material(s): aluminum
-

Specifications by reference

Reference(s)	M39A S	M39A SN	M39A SL	M39A SLN
				
Weight	40 g	40 g	45 g	45 g
Locking system	Without locking system	Without locking system	SCREW-LOCK	SCREW-LOCK
Certification(s)	CE EN 12275 type B, EAC	CE EN 12275 type B, EAC	CE EN 362, CE EN 12275 type B, EAC	CE EN 362, CE EN 12275 type B, EAC
Color(s)	yellow	black	yellow	black
Major axis strength	22 kN	22 kN	22 kN	22 kN
Minor axis strength	8 kN	8 kN	8 kN	8 kN
Open gate strength	7 kN	7 kN	7 kN	7 kN
Gate opening	23 mm	23 mm	20 mm	20 mm
Made in	FR	FR	FR	FR
Guarantee	3 years	3 years	3 years	3 years
Packing	1	1	1	1
Case quantity	30	30	30	30
EAN	3342540817531	3342540817500	3342540817524	3342540817517

Reference(s)	M39A TL	M39A TLN
		
Weight	55 g	55 g
Locking system	TRIACT-LOCK	TRIACT-LOCK
Certification(s)	CE EN 362, CE EN 12275 type B, EAC	CE EN 362, CE EN 12275 type B, EAC
Color(s)	yellow	black
Major axis strength	22 kN	22 kN
Minor axis strength	8 kN	8 kN
Open gate strength	7 kN	7 kN
Gate opening	18 mm	18 mm
Made in	FR	FR
Guarantee	3 years	3 years
Packing	1	1
Case quantity	30	30
EAN	3342540817494	3342540817487

Related product(s) RIG
I'D S
GRILLON