


Universe	Professional
Type	Verticality
Category	Descenders
Subcategory	Mechanical Prusik for tree care



ZIGZAG® PLUS

The ZIGZAG PLUS mechanical Prusik allows the user to move around efficiently in a tree using classic Prusik pulley system technique. The friction chain provides precision and fluidity when moving around. The pulley is mounted on sealed ball bearings to allow the slack to be taken up easily. Can be used on either doubled ropes or a single rope, providing great versatility. The lower attachment hole with high-efficiency swivel ensures stable and correct positioning of the mechanical Prusik and optimal rope glide through the device.



Rope feed is smooth and precise thanks to the release lever, allowing the user great control over his/her movements. Adjusting the pressure on this lever controls the speed of movement.



The lower attachment hole with high-efficiency swivel ensures stable and correct positioning of the mechanical Prusik and optimal rope glide through the device.



Upper attachment hole has a flexible positioning ring that helps keep the connector oriented along its major axis.



The ZIGZAG PLUS mechanical Prusik is used on either doubled ropes or a single rope, thanks to the CHICANE accessory, which offers more friction on the descent, and the KNEE ASCENT assemblies, which facilitate the ascent.

Short Description Mechanical Prusik with high-efficiency swivel, for tree care

Selling Points

- Intuitive grip:
 - technique identical to classic Prusik pulley system
 - the device locks automatically on the rope once the friction chain extends
- For efficient movement within the tree:
 - rope feed is smooth and precise thanks to the release lever, allowing the user great control over his/her movements. Adjusting the pressure on this lever controls the speed of movement
 - easy to take up slack, thanks to the pulley mounted on sealed ball bearings and the separated and curved side plates
 - lower attachment hole with high-efficiency swivel ensures stable and correct positioning of the mechanical Prusik and optimal rope glide through the device
- Versatile:
 - for use on either doubled ropes or a single rope, thanks to the CHICANE accessory, which offers more friction on the descent, and the KNEE ASCENT assemblies, which facilitate the ascent
 - upper attachment hole for the rope end when using a doubled rope or for the CHICANE auxiliary braking device when using a single rope. It has a flexible positioning ring that helps keep the connector oriented along its major axis
 - auxiliary attachment hole for adding a ZILLON lanyard or connecting a second system
- Durability:
 - steel construction for improved durability
 - separated and curved side plates for better wear resistance
- Rope compatibility: 11.5 to 13 mm diameter
- ZIGZAG PLUS allows the user to work in compliance with the ANSI Z133 standard

Specification

- Material(s): aluminum, steel, nylon
 - Weight: 425g
 - Rope compatibility: EN 1891 type A low stretch kernmantel ropes
 - Working load limit: 140 kg
 - Certification(s): CE
-

Specifications by reference

Reference(s)	D022BA00
Color(s)	yellow
Rope compatibility	11.5 to 13 mm
Made in	FR
Guarantee	3 years
Packing	1
Case quantity	10
EAN	3342540826557

Accessory(ies) CHICANE
KNEE ASCENT LOOP
KNEE ASCENT CLIP

Related product(s) STRATO VENT
ZILLON