

HARNESS & SHOCK ABSORBING LANYARD

INSPECTION CHECKLIST

1896					'	NSPECI	ION CF	IECr	\LI\	וכ
Employee (Print):					Inspected By (Prin	t):				
Signature:					Signature:					
Date:					Date:					
Date.					Date.			•		
FULL BODY HARNESS INSPECTION										
WEBBING	PASS	FAIL	NOTE		8			1		
Cuts / Burns or Charring							Luck			
Abrasions / Broken Fibers / Swelling										
Kinks / Cracks / Holes										
Excessive Wear / Discoloration / Chemical or Physical Exposure										
Loose, Cut or Missing Stitching						A		64		
Chest Strap Hook & Loop Have Sufficient Adhesion					1	V				
Evidence of Shock Load to Harness								,		
HARDWARE	PASS	FAIL	NOTE	Notes:						
Cracks / Nicks										
Distorted / Bent										
Moderate to Severe Rust / Corrosion										
Quick Connect Buckles Operate Properly										
ВИСКИВНАМ	Mag.			SHOCK	ABSORBING		INSPECT	ION		
E DUCK					WEBE	SING		PASS	FAIL	NOTE
		8		Cuts / Burn	s or Charring			ш	Ш	
P OF THE STATE OF	Mar.			Abrasions /	Broken Fibers / Sw	elling				
Co. S. Co. Co. Co. Co. Co. Co. Co. Co. Co. Co	Mary Con			Kinks / Cra						
				Excessive V Exposure	Wear / Discoloration	/ Chemical or	Physical			
Notes:			-	Loose, Cut	or Missing Stitching	ı				
			-	Evidence o	f Shock Loading					
			-		HARDV	WARE		PASS	FAIL	NOTE
			- [Cracks / Ni	cks					
			_	Distorted /	Bent					
			_	Moderate t	o Severe Rust / Cor	rosion				

Locking Connectors Operate Freely & Smoothly

Locking Mechanism Functions Properly

If any of these conditions exist, report to your supervisor.

NOTE: Maximum length from users back to bucket truck attachment point is 6'

For questions on use or inspection, please contact our customer service department at

1-800-YES-BUCK or visit our website at www.BuckinghamMFG.com