

MRS (Moving Rope System) attachment point

Rated auxiliary attachment point for second system or work positioning

- and -

SRS ascent harness/chest harness attachment point

Primary user attachment point

Lower plate release button for easy mid-line access



Unique proprietary upper plate locking mechanism for easily opening & closing upper plates for mid-line access




Unique tool-less friction adjustment mechanism for changing between an SRS system and MRS system \*\*No other adjustments are needed when changing rope diameters (11mm - 13mm diameter rope capacity)

## PATENT PENDING



- Proprietary dual articulating and self-adjusting cam system, specifically designed for maximum friction control. For use on 11mm 13mm climbing lines.
- The Throttle includes our new Rope Capture Technology™, which helps prevent the potential of the rope inadvertently coming out of device.









The Throttle is the highest quality and most versatile mechanical rope climbing device ever seen and was designed to deliver, perform, and grow with users at all levels of Arboriculture.

## **Easy to learn Intuitive Design**

Unlike current devices available, The Throttle is the most user friendly, fully featured mechanical rope climbing device.

## **Durability / Product Lifespan**

- Components are manufactured using 304 Stainless Steel and 7075-T6 Aluminum with Premium Grade HardCoat Anodized.
- Rope Wear Components are modular and can easily be replaced.

## PATENT PENDING







