

BUCKINGHAM
BUCK
1896

HARNESS / Available in S, M, L & XL

BUCKTECH™ HARNESS

Introducing the newly redesigned BuckTech™. Now featuring a redesigned seat attachment, providing more comfort and less pressure on the hips when suspending. With the seat, the BuckTech™ is perfect for flying and suspension. Remove the seat and you gain the mobility for the jobs that require a lot of movement. The BuckTech™ is taking tower safety to the next level. The BuckTech's™ removable seat, lightweight aluminum D-Rings, quick connect buckles and much more make this harness one of the most versatile harnesses on the market.

Features Include:

- Now features a redesigned seat attachment that provides more comfort and less pressure in the hips when suspending. With the seat, the BuckTech™ is perfect for flying/helicopter work and suspension.
- Remove the seat and you gain the mobility for the jobs that require a lot of movement.
- Low profile sternal D-Ring for use w/mobile fall arrestors & rope grabs.
- Chest strap adjustment buckles allow user to properly position sternal D-Ring to prevent sliding during fall.
- The seat attachment is now lower on the belt portion, making the harness more comfortable and easier to change out.
- Different color D-Rings allow to easily differentiate between the four.
- Aluminum hip & seat D-Rings reduce overall weight for added comfort.
- Adjustable shoulder straps allow for proper position of dorsal D-Ring.
- Quick connect chest and leg straps make donning a breeze.
- The Belt strap can easily be removed to add tool or bolt bags.
- The dual breakaway loops at waist level provide storage for lanyard hooks when not in use.
- Storage for gear and tools is also located on the rear gear loops.
- Padded shoulder straps & lumbar support provided for all day comfort.
- Padded broad shoulder strap to more evenly distribute weight of gear.
- Gear loops are rated to 100 lbs.
- Full floating suspension D-Ring on web bridge eliminates use of a spreader snap and allows for more mobility when working off the floating D-Ring on bridge.
- Removable bridge for extra mobility.
- Fully padded 7" Drilex back pad.



Arc Tested BuckTech™ Tower Harness 68K966K6

Made from FR (FLASH Resistant) fabric meeting all ASTM-F887 Arc Flash Requirements.

**Buck LeverJust™ w/
Treblekern Tough Rope™
92CM8-8**

**One-handed adjustment while under load;
eliminates need for a wear guard.**



A light weight Adjustable Positioning Lanyard (APL) designed specifically to allow users to lengthen without removing weight from the lanyard with the use of Buckingham's all new LeverGrab™ Length Adjusting Device (LAD), aluminum hardware and a wear resistant TrebleKern rope.

Buckingham's new wear-resistant Tough Rope is constructed with an energy absorbing nylon core, red braided polyester inner core cover (red wear indicator) and an abrasion and heat resistant Technora outer jacket that eliminates the need for a wear guard. No more jamming of your wear guard!

The new Buckingham LeverGrab™ LAD allows for easy one-handed adjustment. This lightweight APL is easy to use and specially designed for use on Towers, Substation and any structure where wear is an issue.

**Buck LeverJust™
9M8-8**

**Allows for one-handed adjustment while
under load.**



The Buck LeverJust™ is a lightweight, all aluminum adjustable positioning lanyard. Featuring Buckingham's new LeverGrab™, a one-handed length adjusting hardware device for easy adjustments under load, when climbing or working. Ideal for Ladder work, secondary use on a pole, substation work, or anything involving steel structures. Key features include:

- 1/2" Kernmantle rope with red warning center to alert user of excessive wear
- Stitched eye allows user to stow excess tail on a BuckTender or handline hook
- Easily used with your left or right hand
- Adjustable when under load—great for rescue and makes length adjustments easier than ever
- The Buck LeverGrab™ works with 7/16" Kernmantle rope, 7/16" TrebleKern Tough Rope
- Aluminum snap hook and carabiner reduce overall weight and meet ANSI requirements for 3600lb. gates
- Meets all applicable ANSI, OSHA and ASTM standards

Available sizes: 6', 7', 8', 9', and 10'. Please contact Buckingham for additional sizes or styles.

Upgrade to TrebleKern Tough Rope, which is nearly indestructible by ordering part number **92CM8-8**.

**BuckAdjuster™ w/Aluminum
Snaphook & Super Fabric Protector
9A4+R-8**

**With a Super Fabric sleeve for protection
from excessive wear.**



Aluminum snap hook and carabiner meet ANSI requirements for 3600lb. gates. Twisted eye length adjusting device for proper orientation on the user's body belt. Overall length is 8'. Meets applicable ANSI, OSHA and ASTM standards.

**BuckAdjuster™ w/Aluminum
Snaphook & Clear Tube Protector
9+R-8**

**Clear plastic tube protects rope
when in use.**



Aluminum snap hook and carabiner that meet ANSI requirements for 3600lb. gates. Stitched eye allows the user to stow excess tail on a handline hook. Clear plastic tube protects the rope when in use. Overall length is 8'. Meets applicable ANSI, OSHA and ASTM standards.

ULTIMATE OX KIT

ULTIMATE OX KIT 50061K21

FULLY CUSTOMIZABLE!

Contact us at
sales@buckinghammfg.com
to customize.

The Ultimate Ox Kit is a complete rigging system that puts numerous rigging options at the user's fingertips. For example, the user can create a 4-to-1 mechanical advantage on up to a 50' working height. Similarly, the user can create a 5-to-1 mechanical advantage on up to a 35' working height. The Ultimate Ox Kit fits in a small, self-contained bag and can be stored in the back of a truck with ease. The OX BLOCK™ is a rope snatchblock with an integrated friction bar used for: hurtman/self-rescue, lowering, raising, snubbing loads, it allows the rigging professional to handle loads with greater control. When lowering loads, tension is transferred from the worker to the OX BLOCK™. The patent pending OX BLOCK™ replaces standard handline blocks, parted blocks and various snatch blocks. Has greater WLLs than blocks of similar size. When configured with optional pulleys, the OX BLOCK™ can be used to create a 4:1, 5:1 or 6:1 mechanical advantage reducing the amount of force needed to lift heavy loads. The advantage of the pulleys used by Buckingham is the swivel side plate that allows for quick and easy rope installation without removing the pulley from the connecting device. The OX BLOCK™ is ASME B30 Compliant.

INCLUDES:



OX BLOCK™ Swivel Eye & Carabiner w/4' Sling
50061A-4
Qty: 1



OX BLOCK™
50061
Qty: 1



Buck Side Swivel Single Sheath
50071B1
Qty: 1



Rope Bag
4569G4P-150
Qty: 1



250' Rope
39SAM27Q2-250
Qty: 1



Steel Triple Action Carabiner
5005S3
Qty: 4



BuckLink™ Sling
3903S-6
Qty: 1



Prusik Loop w/Aluminum Ring
P9J8V+M-34
Qty: 2



Buck Side Swivel Double Sheath
50071B2
Qty: 2

PULLEYS, MOBILE FALL ARREST

PULLEYS



OX BLOCK™ Swivel Eye 50061

A rope snatchblock with an integrated friction bar used for hurtman/self rescue, lowering, raising and snubbing loads.

WLL: 1500 lbf.



OX BLOCK™ Clevis Top w/Buck Pin 50063

Buckingham's OX BLOCK™ Clevis Top with the newest addition, the Buck Pin. Makes the change out of accessories easier than ever before!

WLL: 1500 lbf.



Buck Pin 223892R

An SLIC Pin specifically customized to fit our OX clevis top. The Buck Pin allows the user to add or remove accessories more quickly and easily than the shoulder bolt does.



BuckRigger™ Single 5007R1

Single sheave pulley with swivel eye. 1/2" rope capacity.

WLL: 1800 lbf.



BuckRigger™ Double 5007R2

Double sheave pulley with swivel eye. 1/2" rope capacity.

WLL: 1800 lbf.



BuckSorber™2 400000X12

The BuckSorber™2 is compatible with mobile fall arrest devices and designed to keep peak impact forces below 1350lbs during a 2.5' max fall. The BuckSorber™2 has a max user rating of 350lbs. or two person rating of up to 620lbs. when used for rescue. Rubber lined eyes keep BuckSorber™2 properly oriented on carabiners. *The BuckSorber™2 meets/exceeds ANSI Z359.13 requirements, ASTM F887, OSHA 1926.502 & 1926.954.*

- Arc Flash tested to 40cal/cm², manufactured with Kevlar Webbing
- Cover can be opened for easy inspection
- Specially designed eyes on the BuckSorber™2 keeps the carabiners properly oriented to prevent cross loading the gate
- Can be ordered already attached to Mobile Fall Arrestor 5004L4 (see below) or connected between anchor and lifeline



Mobile Fall Arrestor 5004L3

Fits 1/2" & 7/16" Kernmantle rope. High quality aluminum alloy. Rolling cam for better braking. Device moves freely up and down rope until a fall occurs. Steel ANSI rated triple action carabiner.



Mobile Fall Arrestor Lock w/BuckSorber™2 5004L4

Designed to facilitate manipulations during rope ascents. Used in conjunction with a BuckSorber™2 to work at a distance from the rope. Connection arm makes system loss-resistant when passing intermediate anchors. The Mobile Fall Arrestor locks on rope and stops user. Integrated locking function allows user to immobilize device to reduce length of fall. Moves freely along rope without any manual intervention. *To be used with the BuckSorber™2.*

MISC.




**Anchor Strap
w/Wear Guard**
3904

Designed to be used as a personal anchor for human support. Features a choking configuration and is small, lightweight, and flexible making it easy to handle in the field. Available in green, model **3904J12**.



BuckLink™ Sling
3903S-6

The BuckLink™ is made of lightweight Spectra material and each loop is rated to 5000lbs. With 16 loops, users can adjust the BuckLink™ sling to form a rated anchor of any size and help tackle any situation or need they encounter while in the field.



Buck Tool Tether
600071

The Buck Tool Tether keeps your tools secured and close. Expands smoothly with the user's reach to reduce fatigue and contracts easily to the original length when not in use. Helps workers prevent injury, damage, and lost productivity from dropped tools.



**BuckTender™
Single Leg**
2404

Keeps excess slack from tail of the BuckAdjust™ secondary lanyard or wood pole fall restriction device out of the way while climbing and working. Will break away when approximately 50lbs. of force is applied.



**BuckTender™
Dual Leg**
2404D

Keeps excess slack from tail of the BuckAdjust™ secondary lanyard or wood pole fall restriction device out of the way while climbing and working. Will break away when approximately 50lbs. of force is applied.



**8MM Warpspeed
16" Endless Loop**
P9C8V-10-16S

A 16" long endless loop prusik. 8mm. Dynema Rope. Minimum breaking strength of 5000lbs.



**8MM Warpspeed
30" Eye-to-Eye Prusik**
P9J8V-10-30S

A 30" long eye-eye prusik. 8mm. Dynema Rope. Minimum breaking strength of 5000 lbs.



Adjustable Rope Foot Sling
5004S2

Designed to be attached to a handled ascender. For use in ascending single lines.



Gated Handline Carrier
2402G

Includes hole to easily secure to body belt with bolt or zip tie (zip tie included). Carrier will straighten when approx. 25lbs. of pressure is applied and up to 35lbs. when gate is closed.



Heavy Duty Gated Handline Carrier
2402GH

Includes hole to easily secure to body belt with bolt or zip tie (zip tie included). Carrier will straighten when approx. 33lbs. of pressure is applied and up to 43lbs. when gate is closed.



BuckCarrier™ Chainsaw Carrier
2402B

The lowest profile chainsaw hook on the market, this lightweight aluminum carrier and its compact design can be used to carry practically anything!